



AB 4-22 T/Td ALL-IN ONE OIL INJECTED FIXED SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AB 4 T AB 4 Td	4.5/6	100psi 125psi 150psi 175psi	28.81 25.65 24.18 21.57	W:27.7" L:68.2" H:61.9" W:30.7" L:43.31" H:61.9"	861 941	71
AB 5 T AB 5 Td	5.5 / 7	100psi 125psi 150psi 175psi	34.73 32.43 28.55 26.66	W:27.7" L:68.2" H:61.9" W:30.7" L:43.31" H:61.9"	861 941	71
AB 7 T AB 7 Td	7.5 / 10	100psi 125psi 150psi 175psi	45.76 42.17 36.58 33.41	W:27.7" L:68.2" H:61.9" W:30.7" L:43.31" H:61.9"	889 969	71
AB 11 T AB 11 Td	11 / 15	100psi 125psi 150psi 175psi	69.77 61.98 55.61 50.25	W:30.00" L:73.30" H:70.30" W:35.10" L:73.30" H:70.30"	967 1077	71
AB 15 T AB 15 Td	15 / 20	100psi 125psi 150psi 175psi	101.03 91.62 80.00 72.68	W:30.00" L:73.30" H:70.30" W:35.10" L:73.30" H:70.30"	1007 1142	71
AB 18 T AB 18 Td	18.5 / 25	100psi 125psi 150psi 175psi	123.86 110.75 101.53 89.13	W:37.05" L:92.10" H:81.30" W:39.48" L:92.10" H:81.30"	1573 1743	72
AB 22 T AB 22 Td	22 / 30	100psi 125psi 150psi 175psi	133.15 125.88 119.35 107.44	W:37.05" L:92.10" H:81.30" W:39.48" L:92.10" H:81.30"	1608 1808	72

- * MULTI RIB V-BELT DRIVE
- * 208-230/460 Volt TEFC MOTOR
- * UL Cert ELECTRICAL PANEL
- * ASME Cert SEP TANK & AIR RECEIVER
- * DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE AIR FILTER (AB11-22)
- * ON/OFF COOLING TEFC FAN MOTOR
- * TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK9 (AB11-22)
- * DOE COMPLIANT.
- * INTEGRATED AIR DRYER
- * INTEGRATED LINE FILTERS
- * TIMER DRAIN
- * 214 PSI OPTIONS



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first.
 5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on
 Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids