



AD 11-22 V OIL INJECTED VARIABLE SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW Min cfm - Max cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AD 11 V	11 / 15	100psi	23.77 - 68.92	W:30.08" L:43.31" H:45.16"	850	71
		125psi	23.40 - 61.19			
		150psi	23.10 - 55.22			
		175psi	22.51 - 49.26			
AD 15 V	15 / 20	100psi	57.93 - 105.37	W:30.08" L:43.31" H:45.16"	892	71
		125psi	56.98 - 94.94			
		150psi	55.97 - 84.19			
		175psi	54.74 - 75.37			
AD 18 V	18.5 / 25	100psi	57.93 - 124.15	W:32.05" L:47.24" H:50.08"	1053	72
		125psi	56.98 - 113.45			
		150psi	55.97 - 102.34			
		175psi	54.74 - 92.37			
AD 22 V	22 / 30	100psi	57.93 - 143.57	W:32.05" L:47.24" H:50.08"	1088	72
		125psi	56.98 - 133.16			
		150psi	55.97 - 122.27			
		175psi	54.74 - 111.90			

- * DIRECT DRIVE
- * DANFOSS HEAVY DUTY VFD DRIVE
- * 460 Volt TEFC MOTOR
- * UL Cert ELECTRICAL PANEL
- * ASME Cert SEP TANK
- * DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE AIR FILTER
- * ON/OFF COOLING TEFC FAN MOTOR
- * TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK9
- * DOE COMPLIANT.



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first
 5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids