



AD 30-55 G OIL INJECTED FIXED SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW Min cfm - Max cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AD 30 G	30 / 40	100psi 125psi	212.52 199.02	W:35.98" L:59.80" H:67.60"	1880	73
AD 37 G	37 / 50	100psi 125psi	249.56 243.17	W:35.98" L:59.80" H:67.60"	1905	74
AD 45 G	45 / 60	100psi 125psi	314.22 288.64	W:43.86" L:66.93" H:77.83"	1053	75
AD 55 G	55 / 75	100psi 125psi	414.43 363.25	W:43.86" L:66.93" H:77.83"	1088	75

- * DIRECT GEAR DRIVE
- * 460 Volt TEFC MOTOR
- * UL Cert ELECTRICAL PANEL
- * ASME Cert SEP TANK
- * DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE AIR FILTER
- * ON/OFF COOLING TEFC FAN MOTOR
- * TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK26
- * DOE COMPLIANT.



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first
 5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids

