



## AD 30-55 V OIL INJECTED VARIABLE SPEED AIR COMPRESSORS

| MODEL   | POWER<br>kW/hp | PRESSURE<br>psi | FLOW<br>Min cfm - Max cfm | DIMENSIONS<br>inch         | WEIGHT<br>lbs | NOISE<br>db |
|---------|----------------|-----------------|---------------------------|----------------------------|---------------|-------------|
| AD 30 V | 30 / 40        | 100psi          | 118.66 - 219.03           | W:35.98" L:59.80" H:67.60" | 1880          | 73          |
|         |                | 125psi          | 117.13 - 198.83           |                            |               |             |
|         |                | 150psi          | 115.78 - 181.58           |                            |               |             |
|         |                | 175psi          | 115.21 - 163.92           |                            |               |             |
| AD 37 V | 37 / 50        | 100psi          | 118.66 - 247.97           | W:35.98" L:59.80" H:67.60" | 1905          | 74          |
|         |                | 125psi          | 117.13 - 240.01           |                            |               |             |
|         |                | 150psi          | 115.78 - 220.39           |                            |               |             |
|         |                | 175psi          | 115.21 - 196.95           |                            |               |             |
| AD 45 V | 45 / 60        | 100psi          | 113.72 - 341.16           | W:43.86" L:66.93" H:77.83" | 1053          | 75          |
|         |                | 125psi          | 111.27 - 303.84           |                            |               |             |
|         |                | 150psi          | 108.83 - 276.83           |                            |               |             |
|         |                | 175psi          | 106.55 - 250.99           |                            |               |             |
| AD 55 V | 55 / 75        | 100psi          | 113.72 - 405.09           | W:43.86" L:66.93" H:77.83" | 1088          | 75          |
|         |                | 125psi          | 111.27 - 359.4            |                            |               |             |
|         |                | 150psi          | 108.83 - 324.6            |                            |               |             |
|         |                | 175psi          | 106.55 - 217.8            |                            |               |             |

- \* DIRECT DRIVE
- \* DANFOSS HEAVY DUTY VFD DRIVE
- \* 460 Volt TEFC MOTOR
- \* UL Cert ELECTRICAL PANEL
- \* ASME Cert SEP TANK
- \* DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE AIR FILTER
- \* ON/OFF COOLING TEFC FAN MOTOR
- \* TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK26
- \* DOE COMPLIANT.



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first  
 5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids

