



AB 11-37 OIL INJECTED FIXED SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AB 11	11 / 15	100psi	69.77	W:30.08" L:43.31" H:45.16	842	71
		125psi	61.98			
		150psi	55.61			
		175psi	50.25			
AB 15	15 / 20	100psi	101.03	W:30.08" L:43.31" H:45.16	882	71
		125psi	91.62			
		150psi	80.00			
		175psi	72.68			
AB 18	18.5 / 25	100psi	123.86	W:32.05" L:47.24" H:50.0	1043	72
		125psi	110.75			
		150psi	101.53			
		175psi	89.13			
AB 22	22 / 30	100psi	133.15	W:32.05" L:47.24" H:50.0	1078	72
		125psi	125.88			
		150psi	119.35			
		175psi	107.44			
AB 30	30 / 40	100psi	207.32	W:35.98" L:53.15" H:58.3!	1640	73
		125psi	197.79			
		150psi	173.82			
		175psi	159.78			
AB 37	37 / 50	100psi	234.27	W:35.98" L:53.15" H:58.3!	1693	73
		125psi	218.25			
		150psi	198.88			
		175psi	189.56			

- * MULTI RIB V-BELT DRIVE
- * 208-230/460 Volt TEFC MOTOR
- * UL Cert ELECTRICAL PANEL
- * ASME Cert SEP TANK
- * DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE AIR FILTER
- * ON/OFF COOLING TEFC FAN MOTOR
- * TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK9
- * DOE COMPLIANT.
- * 214 PSI OPTIONS



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first.

5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids