



AD 11-22 V OIL INJECTED VARIABLE SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW Max cfm-Min cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AD 11 V	11 / 15	100	76.42-34.98	W:30.08" L:43.31" H:45.16	850	71
		125	66.79-33.97			
		150	59.05-32.98			
		175	53.02-31.50			
AD 15 V	15 / 20	100	104.60-53.60	W:30.08" L:43.31" H:45.16	892	71
		125	91.77-52.90			
		150	92.00-52.52			
		175	81.80-51.74			
AD 18 V	18.5 / 25	100	128.82-53.60	W:32.05" L:47.24" H:50.0	1053	72
		125	114.05-52.90			
		150	102.08-52.52			
		175	92.88-52.47			
AD 22 V	22 / 30	100	143.57-72.24	W:32.05" L:47.24" H:50.0	1088	72
		125	133.16-70.76			
		150	122.27-69.53			
		175	111.90-68.55			

- * DIRECT DRIVE
- * DANFOSS HEAVY DUTY VFD DRIVE
- * 460 Volt TEFC MOTOR
- * UL Cert ELECTRICAL PANEL
- * ASME Cert SEP TANK
- * DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE AIR FILTER
- * ON/OFF COOLING TEFC FAN MOTOR
- * TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK9
- * DOE COMPLIANT.



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first.

5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids