



AD30-110 V OIL INJECTED VARIABLE SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW Max cfm-Min cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AD 30 V	30 / 40	100	219.03-118.66	W:35.98" L:59.80" H:67.60	1880	74
		125	198.83-117.13			
		150	181.58-115.78			
		175	163.92-115.21			
AD 37 V	37 / 50	100	247.97-118.66	W:35.98" L:59.80" H:67.60	1905	75
		125	240.01-117.13			
		150	220.39-115.78			
		175	196.95-115.21			
AD 45 V	45 / 60	100	341.16-113.72	W:45.98" L:78.40" H:71.65	2935	76
		125	303.84-111.27			
		150	276.83-108.83			
		175	250.99-106.55			
AD 55 V	55 / 75	100	405.09-113.72	W:45.98" L:78.40" H:71.65	2990	77
		125	359.40-111.27			
		150	324.60-108.83			
		175	217.80-106.55			
AD 75 V	75 / 100	100	455.71-181.18	W:48.11" L:84.65" H:75.59	4410	77
		125	445.71-184.87			
		150	430.69-188.65			
		175	397.68-192.50			
AD 90 V	90 / 125	100	640.81-345.66	W:53.66" L:90.00" H:84.01	6112	78
		125	582.85-352.73			
		150	523.90-359.93			
		175	479.29-367.28			
AD 110 V	110 / 150	100	766.82-467.65	W:53.66" L:90.00" H:84.01	6396	79
		125	678.71-477.20			
		150	600.19-486.91			
		175	541.51-496.88			

- * DIRECT DRIVE
- * DANFOSS HEAVY DUTY VFD DRIVE
- * 460 Volt IE3 TEFC MOTOR(30-55kW)
- * 460 Volt IE4TEFC MOTOR(75-110kW)
- * UL Cert ELECTRICAL PANEL
- * ASME Cert SEP TANK
- * DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE INLET FILTER

- * ON/OFF CENTREFIGUAL COOLING SYSTEM DRIVEN BY TEFC FAN MOTOR
- * TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK26
- * DOE COMPLIANT.



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first.

5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids