AD 11-22 V OIL INJECTED VARIABLE SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW Max cfm-Min cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AD 11 V	11 / 15	100 125 150 175	76.42-34.98 66.79-33.97 59.05-32.98 53.02-31.50	W:30.24" L:46.18" H:45.35"	850	71
AD 15 V	15 / 20	100 125 150 175	104.60-53.60 91.77-52.90 82.00-52.52 81.80-51.74	W:30.24" L:46.18" H:45.35"	892	71
AD 18 V	18.5 / 25	100 125 150 175	128.82-53.60 114.05-52.90 102.08-52.52 92.88-52.47	W:32.13" L:50.09" H:50.28"	1053	72
AD 22 V	22 / 30	100 125 150 175	143.57-72.24 133.16-70.76 122.27-69.53 111.90-68.55	W:32.13" L:50.09" H:50.28"	1088	72

* DIRECT DRIVE
* DANFOSS HEAVY DUTY VFD DRIVE
* 460 Volt TEFC MOTOR
* UL Cert ELECTRICAL PANEL
* ASME Cert SEP TANK
* DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE AIR FILTER
* ON/OFF COOLING TEFC FAN MOTOR
* TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK9
* DOE COMPLIANT.

Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first.

5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids