AD30-110 V OIL INJECTED VARIABLE SPEED AIR COMPRESSORS

MODEL	POWER kW/hp	PRESSURE psi	FLOW Max cfm-Min cfm	DIMENSIONS inch	WEIGHT lbs	NOISE db
AD 30 V	30 / 40	100 125 150 175	219.03-118.66 198.83-117.13 181.58-115.78 163.92-115.21	W:37.80" L:59.80" H:67.80	1880	75
AD 37 V	37 / 50	100 125 150 175	247.97-118.66 240.01-117.13 220.39-115.78 196.95-115.21	W:37.80" L:59.80" H:67.80	1880	75
AD 45 V	45 / 60	100 125 150 175	341.16-113.72 303.84-111.27 276.83-108.83 257.82-106.55	W:46.10" L:78.74" H:71.65	2935	76
AD 55 V	55 / 75	100 125 150 175	405.09-113.72 359.40-111.27 324.60-108.83 321.00-106.55	W:46.10" L:78.74" H:71.65	2990	77
AD 75 V	75 / 100	100 125 150 175	541.83-249.45 497.35-247.51 458.52-244.81 419.15-241.88	W:48.11" L:84.65" H:75.59	4410	77
AD 90 V	90/ 125	100 125 150 175	640.81-367.28 582.85-367.28 523.90-367.28 470.29-367.28	W:53.66" L:90.00" H:84.0	6112	78
AD 110 V	110 / 150	100 125 150 175	766.82-496.88 678.71-496.88 600.19-496.88 541.51-496.88	W:53.66" L:90.00" H:84.0	6396	79

* DIRECT DRIVE
* DANFOSS HEAVY DUTY VFD DRIVE
* 460 Volt IE3 TEFC MOTOR(30-55kW)
* 460 Volt IE4TEFC MOTOR(75-110kW)
* UL Cert ELECTRICAL PANEL
* ASME Cert SEP TANK
* DEEP IN TYPE SEPARATOR FILTER, DOUBLE STAGE INLET FILTER

* ON/OFF CENTREFIGUAL COOLING SYSTEM DRIVEN BY TEFC FAN MOTOR
* TFT TOUCH SCREEN LOGIC CONTROLLER LOGITRONIK26
* DOE COMPLIANT.



Standard Warranty Period- Bumper to bumper, 12 months from start-up or 18 month from shipment, whichever occurs first.

5-year Extended Warranty Coverage- Air end, Drive Motor, Heat Exchanger, Separator Tank Backed by Orange Trust-Built on Dependability

Warranty coverage is valid only with an Authorized Start-up and the use of genuine parts and fluids